



DRILL RIGS

CDR 132 & CDR 162

ø 130 or
160mm

6-7kg



415-545mm



CDR 132



CDR 162



Fully aluminum drill stand combining rigidity, precision, ease of use and light weight. Unique accurate and smooth guiding thanks to 4 guiding rolls made of high performance Nylon. Easily accessible guiding wheels for wear compensation adjustment.

Features

Benefits

Aluminium column.	• Robust, reliable while light weight.
Left and right mounting drive-lever.	• Easy use even in confined environments.
Multi-purpose drive-lever.	• Can be used for levelling and locking screws.
Spirit level.	• For accurate column levelling.
Rolls-guided carriage.	• High accuracy drill guiding, few maintenance.
Laser pointer (CDR162).	• For precise rig positioning.
Ring mounting motor collar (60mm).	• Quick and easy motor mounting without any additional tool.
Transport handle on top.	• Easy and ergonomic handling.
Adjustable bit guide (CDR162).	• Precise cutting of the bit.



Spirit level.



Laser pointer system
(CDR162).



Adjustable bit guide
(CDR162).



Left and right
mounting drive lever

DRILL RIG for collar mounting

MODELS	CDR 82V	CDR 132	CDR 162
Item No	3103 87339	3103 87338	3103 87340
EAN 13 Code	5450248 466697	5450248 466482	5450248 466703
TECHNICAL DATA			
Diam. Max	80mm	130mm	160mm
Hub	410mm	415mm	545mm
Column	Aluminum	Aluminum	Aluminum
Column section	50 x 50mm	50 x 50mm	50 x 50mm
Base	Vacuum	Dowel	Dowel
Base dimensions	510 x 150mm	215 x 170mm	200 x 250mm
Bit guide	No	No	Yes
Motor mounting plate	Ring 60mm incl.	Ring 60mm incl.	Ring 60mm incl.
Carriage	Aluminum	Aluminum	Aluminum
Carriage Guiding system	Rolls	Rolls	Rolls
Carriage handle	left-right	left-right	left-right
Carriage travel	1:1	1:1	1:1
Braces	No	No	Yes
Tilting	No	No	0-45°
Pointing laser	No	No	Yes
Spirit level	1	1	1
Transport wheels	No	No	Optional
Height	720mm	725mm	900mm
Weight	7,5kg	6kg	7kg

CDR 82V

ø 80mm
 7,5kg

 410mm



Vacuum base drill rig with manual suction cups. Especially designed for quick mounting on flat and polished supports, such as stone, glass, stair steps, etc.

The aluminium column is pivoting to allow drilling in corners and recessed area.

- 60mm motor collar mounting.
- Rolls guided carriage.
- Left and right mounting drive lever.

D160

ø 32-160mm
 15,5kg
 2,5kW
 1 speed

 650mm



Complete kit including:

- Aluminium column (885mm).
- Swivel base for precise drilling.
- Quick and easy motor mounting without additional tool.
- 2,5kW motor with dual connection 1 1/4" + 1/2".
- Right and left mounting feed mechanism lever.
- PRCD.