

MG 15000 SS-K

+ SUPER SILENCED DIESEL SINGLE-PHASE GENERATOR / OUTPUT POWER 15 KVA SINGLE-PHASE

Gen Set Features	+ Low oil pressure, high coolant temperature, low fuel level, glow plug and battery charger warning lights + 12V built-in battery with electric start + Engine hourmeter + Fuel level gauge + 2 x 230 V - 50 Hz Single-phase outlets protected by circuit breakers + Earth Leakage Circuit Breaker (ELCB) + Hardwire connection + Voltmeter + Emergency STOP button + Central lifting eye / Fork lift pockets		
Gen Set Options (available as factory options)	+ Versions with different voltages + Spark arrester muffler + Engine heaters powered by mains 230V - 50Hz (recommended for AA model) + AMF panel for auto start operation (AA model) + DAS, auto engine protection shutdown system with warning lights in case of: - battery charger failure - high coolant temperature - low fuel level - low oil pressure		
Accessories on Request	+ Lighting Tower + Two-wheels site tow undercarriage (GRT2W)		
Noise Level	+ LWA 94	(69 dB at 7m)	Homologated in accordance with the "Directive 2000/14/CE"
AC Generator - 50 Hz	+ Type	synchronous	
	+ Single-phase Power (stand by)	15 kVA - 230 V	
	+ Single-phase Power (prime)	13,5 kVA - 230 V	
	+ Power Factor	0,8	
Diesel Engine 3000 rpm	+ Type Kubota D1105-E	- 3 cyl. - 24,6 HP (18,1 kWm) - 1123 cm ³	
	+ Fuel	diesel	
	+ Cooling system	water	
	+ Starting system	electric	
	+ Fuel tank capacity	47 l	
	+ Fuel consumption @ 75%	4,9 l/h	
Other Features	+ Insulation Class	H	
	+ Mechanical Protection	IP 23	
	+ Dimensions (L x W x H)	1200 x 700 x 970 mm	
	+ Net Weight	410 kg	

+ MG 15000 SS-K

